

BOE MLED BYH V1 Series



Key Features

- Flip chip, common anode. common cathode optional.
- Ultra thin and light. Thickness 32.7mm and 3.7kg per cabinet.
- Front maintenance magnetic suction structure
- 3-in-1 board design, easy for replacement.

Application Scenarios

Commercial | Public screen | Data center | Exhibition | Conference

BYH-COB	BYH009 V1	BYH012 V1	BYH015 V1
Pitch(mm)	0.9375	1.25	1.5625
MDL size(mm*mm)	150*168.75	150*168.75	150*168.75
Cabinet dimension(mm*mm*mm)	600*337.5*32.7	600*337.5*32.7	600*337.5*32.7
Ambient contrast ratio	7200:1	7700:1	8200:1
Complete set weight(kg)	3.7kg	3.7kg	3.7kg
Maintenance mode	Front	Front	Front
Cabinet flatness(mm)	≤0.1	≤0.1	≤0.1
Avg. power consumption(W/sqm)@600nit	117	95	100
Max. power consumption(W/sqm)@600nit	350	285	300
White balance brightness(cd/m)	Typ-600	Typ-600	Typ-600
Refresh rate(Hz)	3840	3840	3840
Installation mode	Stacking & Wall mounting	Stacking & Wall mounting	Stacking & Wall mounting